

## PVC insulated, non-sheathed cable for automotive, T2 ID (class B)



### Application:

- Wire harness of low-tension electric circuits for automobiles and motorcycles.

### Standard:

- PSA B25 1110
- ISO 6722

### Construction:

- Plain or tinned annealed stranded copper conductor.
- PVC insulation type T2.

### General specification:

- Rated voltage: up to 50 V.
- Working temperature: -40 to +100°C.
- Resistant to heat, cold, abrasion, flame and chemicals.
- Excellent flexibility.
- Available in colors.

PVC insulated, non-sheathed cable for automotive, T2 ID (class B)

Cross-sectional area Nom.	No. of wires x diameter Nom.	Conductor diameter	Insulation thickness	Overall diameter		Weight Approx.	Conductor resistance at 20°C	
				Min.	Max.		Min.	Max.
mm <sup>2</sup>	mm	mm	mm	mm	mm	Kg/km	Ω/km	Ω/km
0.22	7 x 0.20	0.61	0.20	1.15	1.20	3	77.90	84.80
0.35	7 x 0.25	0.77	0.20	1.25	1.35	4	50.00	54.40
0.5	16 x 0.20	0.93	0.20	1.40	1.60	6	34.10	37.10
0.75	24 x 0.20	1.14	0.20	1.60	1.80	8	22.70	24.70
1	32 x 0.20	1.31	0.25	1.75	1.95	11	17.00	18.50
1.5	30 x 0.25	1.59	0.25	2.10	2.25	15	11.70	12.70
2	37 x 0.25	1.76	0.25	2.30	2.50	19	8.66	9.42
2.5	50 x 0.25	2.05	0.30	2.70	2.90	25	6.99	7.60
3	44x 0.30	2.31	0.30	3.00	3.20	31	5.66	6.15
4	56 x 0.30	2.60	0.30	3.40	3.70	41	4.33	4.71
5	70 x 0.30	2.91	0.30	3.70	3.90	48	3.62	3.94
6	84 x 0.30	3.19	0.35	4.10	4.30	60	2.89	3.14
7	105 x 0.30	3.57	0.35	4.30	4.60	70	2.50	2.72

